TECHNICAL DATA

GLASS CLOTH TAPE Product Code: 1G130

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093 E-mail : sales@pleo.com * Web Site : http://www.pleo.com





A UL FILE #E126174

Description :	1G130 is a Glass Cloth Tape with <u>rubber adhesive</u> . It is designed to offer efficiencies in application and versatility in selection.		
Application :	Coil wrap, crossover insulation, coil banding.		
Features/Benefits	Resistance to flagging and varnish solvents. Razor slitting is used to provide fray-free edges.		
Technical Details :	<u>PROPERTIES</u> GLASS CLOTH THICKNESS COLOR TOTAL THICKNESS	<u>UNIT</u> mm - mm	$\frac{\text{SPECIFICATION}}{0.13}$ white 0.170 ± 0.020
	BACKING THICKNESS TENSILE STRENGTH	mm Isa/25mm	0.125
	ELONGATION AT BREAK	kg/25mm %	72.273 8
	ADHESION TO STEEL	kg/25mm	0.852
	BREAKDOWN VOLTAGE	kV	2.5
	TEMPERATURE CLASS	оС	130
Availability:	Standard 55M roll, 3" core, width 600mm		
Shelf Life :	6 months when storage at 23°C and 65% relative humidity		

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.



No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.