TECHNICAL DATA

COPPER FOIL TAPE Product Code: 1ECE7

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone: (852) 2604-8222 * Facsimile: (852) 2693-2093
E-mail: sales@pleo.com * Web Site: http://www.pleo.com



SI UL FILE #E126174

Description: 1ECE7 is a 0.04mm thick Smooth-Backed copper foil with embossed pattern coated

with a non-conductive acrylic pressure sensitive adhesive, good solvent and heat resistant, outstanding adhesion, good solderability. The tape is supplied on a glassine

paper release liner to permit ease of die cutting and application.

Application: Specifically developed for use as Electro-Magnetic Interference (EMI) and

Radio-Frequency Interference (RFI), shielding, in electronic industry such as:

transformer, electronic cables and so on. Also ideal as circuit/boards modification and

repair.

Technical Details: <u>PROPERTIES</u> <u>UNITS</u> <u>SPECIFICATION</u>

COLOR - Bright Copper TOTAL THICKNESS mm 0.07 ± 0.005 COPPER FOIL THICK mm 0.04 ± 0.004

TENSILE STRENGTH kg/25mm 13
ELONGATION % 2
ADHESION TO STEEL kg/25mm 0.75

Test Method: In accordance with <u>ASTM</u> D-1000 method

Shelf Life: 12 months when stored in original carton at 23°C and 65% relative humidity

Availability: Standard 30M roll, 3" core, width 250mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.