## **TECHNICAL DATA**

## NOMEX® ARAMID PAPER TAPE Product Code: 1N008F

## P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 \* Facsimile: (852) 2693-2093 E-mail: sales@pleo.com \* Web Site: http://www.pleo.com



**FL** UL FILE #E126174

Description: 1N008F is NOMEX® paper 2mil (0.05mm) thick coated with Acrylic based adhesive,

excellent Solvent resistant and flame retardant.

Application: For use in construction of transformers and electric motors, coil wrapping, capacitors,

insulation of electrical parts which are to be impregnated and baked. Excellent varnish

absorbability. It is use in Electrical insulation system up to Class H.

Technical Details: <u>PROPERTIES</u> <u>UNITS</u> <u>SPECIFICATION</u>

COLOR - White

TOTAL THICKNESS mm (mil)  $0.09 \pm 0.01$  (3.6)

BACKING THICKNESS mm (mil) 0.05 (2) TENSILE STRENGTH kg/25mm (lb/in) 10(22) ELONGATION % 10

ADHESION TO STEEL kg/25mm (oz/in) 0.5 (17.6)
DIELECTRIC BREAKDOWN kV 2.5

TEMPERATURE RATING °C 155

\*NOMEX is a registered trademark of DUPONT

Test Method: In accordance with <u>ASTM</u> method

Shelf Life: 2 months when storage at 23°C and 65% relative humidity

Availability: Standard 30M roll, 3" core, width 440 mm



