## TECHNICAL DATA

## **NOMEX® ARAMID PAPER TAPE**

**Product Code: 1N03S** (Flame Retardant)

## P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.

Telephone: (852) 2604-8222 \* Facsimile: (852) 2693-2093 E-mail: sales@pleo.com \* Web Site: http://www.pleo.com



1N03S is a 0.075mm thick NOMEX® paper coated with Silicon based adhesive, Description:

excellent Solvent resistant, and flame retardant.

Application: For use in construction of transformers and electric motors, coil wrapping, capacitors,

insulation of electrical parts which are to be impregnated and baked. Excellent varnish

absorbstivity. It is used as insulation material of Class F.

Technical Details: **PROPERTIES UNIT** SPECIFICATION

> **COLOR** white

TOTAL THICKNESS mm (mil)  $0.135 \pm 0.012$  (5.4)

**BACKING THICKNESS** mm (mil) 0.076(3)TENSILE STRENGTH kg/25mm (lb/in) 12 (26)

**ELONGATION** 

ADHESION TO STEEL kg/25mm (oz/in) 1.0(35)DIELECTRIC BREAKDOWN kV 3

**UNWIND FORCE** kg/25mm 0.25 TEMPERATURE CLASS °C 200 INSULATION RESISTANCE  $1.75 \times 10^8$ ohm

\*NOMEX is a registered trademark of DUPONT

Test Method: In accordance with ASTM method

Shelf Life: 2 months when storage at 73F and 65% relative humidity

Standard 30M roll, 3" core, width 440m Availability:







