
TECHNICAL DATA

NOMEX® ARAMID PAPER TAPE

Product Code: 1N155 (Flame Retardant)

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 * Facsimile: (852) 2693-2093 E-mail: sales@pleo.com * Web Site: http://www.pleo.com



SUL FILE #E126174

Description: 1N155 is NOMEX® paper 3mil (0.075mm) thick coated with Acrylic based adhesive,

excellent Solvent resistant and flame retardant.

Application: For use in construction of transformers and electric motors, coil wrapping, capacitors,

insulation of electrical parts which are to be impregnated and baked. Excellent varnish

absorbability. It is use in Electrical insulation system up to Class N.

Technical Details : <u>PROPERTIES</u> <u>UNITS</u> <u>SPECIFICATION</u>

COLOR White 0.12 ± 0.012 TOTAL THICKNESS mm**BACKING THICKNESS** mm 0.075 TENSILE STRENGTH 12 kg/25mm **ELONGATION** 5 ADHESION TO STEEL kg/25mm 0.5

DIELECTRIC BREAKDOWN kV 3 TEMPERATURE RATING °C 155

*NOMEX is a registered trademark of DUPONT

Test Method: In accordance with <u>ASTM</u> method

Shelf Life: 2 months when storage at 23°C and 65% relative humidity

Availability: Standard 30M roll, 3" core, width 440 mm



All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.



