TECHNICAL DATA

POLYESTER FILM/ GLASS FILAMENT TAPE Product Code: 1PG881

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093 E-mail : sales@pleo.com * Web Site : http://www.pleo.com





Description :	#1PG881 Polyester film, glass filament tape coated with high performance <u>rubber</u> adhesive.		
Application :	Good tensile strength and edge tear resistance, good for heavy duty holding applications.		
Features/Benefits :	Both products have tensile strength, designed for holding application in coil manufacturing. Excellent quick tack and non-flagging characteristics.		
Technical Details :	<u>PROPERTIES</u> TOTAL THICKNESS TENSILE STRENGTH ELONGATION ADHESION TO STEEL DIELECTRIC BREAKDOWN HOLDING POWER TEMPERATURE RATING	<u>UNITS</u> mm(mil) kg/25mm(lb/in) % kg/25mm(oz/in) kV mm °C	$\frac{\text{SPECIFICATION}}{0.16 \pm 0.01 (6.5)}$ 45 (99) 10 0.75 (26) 5 0.5 155
Availability :	Standard 55 Meter roll, 3" core, width 975mm		
Shelf Life :	6 months when storage at 23°C and 65% relative humidity		

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.



No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer