TECHNICAL DATA

<u>"PPS" Polyphenylene Sulfide Tape</u> Product Code: 1PPSS

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093 E-mail : sales@pleo.com * Web Site : http://www.pleo.com





SL UL FILE #E126174

- Description : PPS tape #1PPSS is made by PPS (Polyphenylene Sulfide) film backing with silicone adhesive. PPS film with an excellent heat resistance, chemical resistance; and physical strength.
- Application : It is designed for high temperature application of chop type aluminum foil condenser, insulation of the electrodes of lithium ion secondary battery or high temperature transformers and inverter transformers for LCD backlighting.
- PROPERTIES **Technical Details :** UNIT BACKING COLOR ADHSION TAPE TOTAL THICKNESS mm (mil) **BACKING THICKNESS** mm (mil) **TENSILE STRENGTH** kg/25mm (N/10mm) **ELONGATION** % ADHESION TO STEEL kg/25mm(N/10mm) DIELECTRIC BREAKDOWN kV ELECTROLYTIC CORROSION FACTOR INSULATION RESISTANCE ohm TEMPERATURE CLASS °C



Test Method : In accordance with <u>ASTM</u> method

Shelf Life : a6 months when storage at 23°C and 65% relative humidity

Availability : Standard 33M & 50 M roll, width from 2mm and up is available



Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warantices, express or implied: Seller's and manufacturer's only obligations hall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.