TECHNICAL DATA

PVC ELECTRICAL INSULATING TAPE Product Code: 1V808

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 * Facsimile: (852) 2693-2093 E-mail: sales@pleo.com * Web Site: http://www.pleo.com



91 UL FILE #E126174

Description : A plasticized polyvinyl chloride (PVC) film, giving excellent conformability and

flexibility, coated with an aggressive Rubber-Resin adhesive with good ageing

characteristics. No flagging or deterioration even under temperature as high as 80°C.

Flame retardant, cold and weather resistant. UL listed and CSA certified.

Application: For use as electrical insulation on joints and splices in wires and cables in accordance

with the National Electrical Code.

UL-510

Technical details: PROPERTIES UNITS REQUIREMENTS

Shelf life: 12 months when stored at 73°F and 65% relative humidity

Availability: Standard 20M roll, 32mm core with UL & CSA markings, width 1240mm

Temp. rating: (1) For use at not more than 80°C, UL-510 specification

(2) -7°C to 80°C, CSA C22.2 no.197 specification

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.