TECHNICAL DATA

KAPTON® POLYIMIDE FILM TAPE Product Code: 1K7270

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 * Facsimile: (852) 2693-2093 E-mail: sales@pleo.com * Web Site: http://www.pleo.com



91 UL FILE #E126174

Description: 1K7270 is a 2 mil polyimide film tape with a silicone thermosetting pressure sensitive

adhesive system.

Application: Designed for use as a high performance insulation layer on coils and fractional

horsepower motors. Excellent for bundling and protective outer wrap applications.

Features/Benefits: Polyimide film backing offers high conformability.

Delivers abrasion protection and puncture resistance at high temperatures.

Performance silicone adhesive system is engineered for high temperature performance

and resists solvent contamination.

Technical Details: PROPERTIES UNITS SPECIFICATION

TOTAL THICKNESS $\overline{\text{mm(mil)}}$ $0.09 \pm 0.005 (3.5)$

TENSILE STRENGTH kg/25mm(lb/in) 30 (65) ELONGATION % 60

ADHESION TO STEEL kg/25mm(oz/in) 0.55 (20)
DIELECTRIC BREAKDOWN kV 8.5

TEMPERATURE RATING °C 180

Color: Amber

Availability: Standard 33 Meter roll, 3" core, width 406mm

Shelf Life: 6 months when storage at 23°C and 65% relative humidity



