POLYESTER FILM TAPE Product Code: 1P133

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093 E-mail : sales@pleo.com * Web Site : http://www.pleo.com





N UL FILE #E126174

0.8

Description : 1P133 is a 1-mil thick polyester film coated with a pressure sensitive Acrylic adhesive high dielectric strength, comfortable, tough and thin, CTI grade PLC=0 as Group 1 materials. Application : Excellent for use in electric application, such as outer wrapping on capacitors and coils, holding transformer construction, harness wrap and so on. It is used as insulation material of class B. **Technical Details :** PROPERTIES UNITS **SPECIFICATION** 0.055 ± 0.005 TOTAL THICKNESS mm **TENSILE STRENGTH** kg/25mm 10 **ELONGATION** % 80

kg/25mm

	DIELECTRIC BREAKDOWN	Kv	5
	TEMPERATURE RATING	°C	130
Color :	LY = Light Yellow (Other color available upon request.)		
Test Method :	In accordance with <u>ASTM</u> method		
Shelf Life :	6 months when storage at 73°F and 65% relative humidity		
Availability :	Standard 66 Meter & 50 Meter roll, 3" core, width 975mm		

ADHESION TO STEEL

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warrantices, express or implied: Seller's and manufacturer's only obligations shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer's shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.



No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.