
## **TECHNICAL DATA**

## **POLYESTER FILM TAPE**

Halogen-Free **Product Code: 1P802** 

## P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 \* Facsimile: (852) 2693-2093 E-mail: sales@pleo.com \* Web Site: http://www.pleo.com



**91** UL FILE #E126174

Description: 1P802 is a polyester film coated with a pressure sensitive Acrylic adhesive, high

dielectric strength, excellent adhesive properties, outstanding heat and Solvent resistant,

high tensile and dielectric strength.

Application: For the insulation and holding applications in transformers, capacitors, electric motors,

relays stabilizers, and various kinds of electronic components. It is used as insulation

material of class B.

Technical Details: **PROPERTIES UNIT SPECIFICATION** 

> TOTAL THICKNESS mm  $0.055 \pm 0.005$

TENSILE STRENGTH 9.5 kg/25mm **ELONGATION** 100 ADHESION TO STEEL kg/25mm 0.6 DIELECTRIC BREAKDOWN kV TEMPERATURE CLASS °C 130

\* Color: TR = transparentBK = blackBG = black (matt black)

WH = white

In accordance with ASTM method Test Method:

Shelf Life: 6 months when storage at 23°C and 65% relative humidity

Standard 50M roll, 3" core, width 960mm - 1240mm Availability:



