TECHNICAL DATA

POLYESTER TAPE Product Code: 1PETS

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093 E-mail : sales@pleo.com * Web Site : http://www.pleo.com





N UL FILE #E126174

Description: 1PETS is polyester film coated with silicone adhesive. Excellent solvent resistant.; heat resistant and quick grab property, tough and conformable over irregular surfaces, outstanding adhesion over the silicone tube and wire. Application : Ideal for insulating, banding, anchoring, holding in motors and transformers. Resists the high temperature of molten solder while leaving minimal residue when removed following the process. Reduces clean-up time without danger of breakage or bath contamination. **Technical Details :** PROPERTIES UNIT **SPECIFICATION** TOTAL THICKNESS mm 0.06 ± 0.005 **TENSILE STRENGTH** kg/25mm 11 ELONGATION % 60 ADHESION TO STEEL kg/25mm 0.63 DIELECTRIC BREAKDOWN kV 5 TEMPERATURE RATING °C 155 Test Method : In accordance with ASTM D-1000 method Shelf Life : 6 months when storage at 73°F and 65% relative humidity Standard 33M & 50Meter roll, 3" core, width 960mm Availability :

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warrantics, express or implied: Seller's and manufacturer's only obligations shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer's shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.



No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.