

技术数据

软质云母片


UL Cat. No. SM61 & SM62 & 8M81

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.

Telephone : (852) 2604-8222 * Facsimile : (852) 3585-3181

E-mail : sales@pleo.com * Web Site : http://pleo.com



UL FILE #E222948

描述 : **SM61 & SM62 & 8M81** 是一种软质云母片, 又称上胶云母纸, 在室温下具有良好弹性和柔韧性, 根据需要可卷曲成各种形状。它是由硅及云母板经特殊配方的有机硅树脂复合而成, 通过 UL94V-0 测试, RTI 200 °C; 并取得 UL 认证, 档案号 E222948。被广泛用于 H 级、C 级、R 级、S 级的高压变压器、工业炉及家用电器上的绝缘。

应用 : **SM61 & SM62 & 8M81** 可以缠绕或包裹无需加热, 可被用作覆盖片、分隔片、绝缘片或者耐高温密封材料。通常使用场合如热风枪、吹风机、暖风机、断路器、变压器、电炉、发电机及电磁线圈绝缘等。

特性 :

- 优异的耐热性可达 1000 °C.
- 优良的电子绝缘.
- 优良的抗拉强度和在室温下容易成形.

技术数据 :		单位	<u>SM62</u>	<u>SM61</u>
			<u>8M81</u>	
	云母纸		银白色	金色
	云母纸厚度	mm	0.15 - 3.0	0.15-3.0
	厚度公差	mm	±10%	±10%
	密度	g/cm ³	≥1.6	≥1.6
	云母含量	%	≥88	≥88
	硅含量	%	≤12	≤12
	电气强度	kV/mm	≥10	≥10
	耐温等级			
	持续使用环境	°C	500	750
	间歇工作环境	°C	550	800



BCtape™ Phobbin® BCwire® BCmica® BCtube® is P. Leo & Co., Ltd. registered trade mark

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.