## 技术数据书

## 聚酯薄膜胶带 产品编号:1P801C

(阻燃性)

## P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 \* Facsimile: (852) 3585-3181 E-mail: sales@pleo.com \* Web Site: www.pleo.com



说明: 1P801C(0.025mm 薄膜)聚酯薄膜胶带是在聚酯薄膜涂覆一层压敏丙烯酸酯胶

粘剂而成, 高介电强度、薄而坚韧。符合 UL510A 阻燃要求。PTC=0, CT1 等

级一

应用: 适用于电器产品, 例如电容器和线圈外层包裹, 稳固变压器结构。属于 B 级绝

缘材料。

技术数据: 性能 单位 规格

> 总厚度  $0.055\pm0.005$ mm

拉伸强度 kg/25mm>9 伸长率 >70 黏着力 >0.8 kg/25mm击穿电压 >5 k۷ 耐热等级 °C 130

测试方法: 根据 ASTM 标准测试

保存期限: 6 个月(温度: 23℃、湿度: 65%)

每卷长 33/50M, 宽 960/1230mm, 卷心直径 3 英寸 包装标准:

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or \*he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

