
## 技术资料书

## 耐高温聚酯 PET 胶带 产品编号:1PETS

## P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone: (852) 2604-8222 \* Facsimile: (852)3585-3181
E-mail: sales@pleo.com \* Web Site: www.pleo.com



说 明: 1PETS 耐高温聚酯 PET 胶带是在聚酯薄膜涂覆一层硅胶粘合剂而成。

优良的抗溶剂、高粘着力、柔软服帖、高耐热性及贴服性、再撕离不留残

胶。

在硅胶管及电线有极佳的粘着效果。

用 途: 专业用于电路板含浸过程中, 遮覆金手指部位,

防止电镀液浸入及污染,保护电路板电镀,超高温烤漆及粉末喷涂等工业。

技术数据: 性能 单位 规格

 基材厚度
 mm
 0.028±0.003

 总厚度
 mm
 0.050±0.005

拉伸强度 MPa ≥120 伸长率 % ≥50 黏着力 N/25mm ≥7.0 击穿电压 kV 2.0

耐溫性 -- 180°C/30min

测试方法: 根据 ASTM 标准测试

保存期限: 6个月(温度: 73°F、湿度: 65%)

包装标准: 每卷长 33M & 66M, 宽 960mm, 卷心直径 3 英寸

顏色 : 透明色 、綠色

## Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or "he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with

