
## TECHNICAL DATA

## **POLYIMIDE FILM TAPE Product Code: 1KPST038**

(Flame Retardant)

## P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 \* Facsimile: (852) 3585 3181 E-mail: sales@pleo.com \* Web Site: www.pleo.com



Description: 1KPST038 is a 0.025mm thick Polyimide film coated with Silicone based thermosetting

> pressure sensitive adhesive. Outstanding, high temperature retention of physical and electrical properties. This product complies with the flame Retardant requirements of

UL 510.

Application: For use in high performance electrical applications, used on high-temperature coils, such

as in traction machine manufacturing, in the production of generators, capacitors

transformers etc.

Technical Details: **SPECIFICATION PROPERTIES UNIT** 

> **COLOR** amber

TOTAL THICKNESS  $0.038 \pm 0.003$ mm

TENSILE STRENGTH kg/25mm >8 **ELONGATION** % >50

ADHESION TO STEEL 0.45 - 0.70kg/25mm **UNWIND FORCE** gf/25mm400-1000

DIELECTRIC BREAKDOWN kV >5  $^{0}C$ TEMPERATURE RATED 200

Shelf Life: 6 months when storage at 73F and 65% relative humidity

Standard 33M roll, 3" core, width 1020 mm Availability:



