## 技术数据书

## 双面胶带 产品编号:1P2DS

## P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 \* Facsimile: (852) 3585-3181 E-mail: sales@pleo.com \* Web Site: www.pleo.com



说明: 1P2DS (0. 025mm PET 薄膜) 双面胶带是在 PET 薄膜涂覆一层压敏丙烯酸酯胶

粘剂,以牛皮纸作离型纸而成。

技术数据: 性能 单位 规格

基材厚度 0.025 mm

总厚度 mm 0.12±0.005

拉伸强度 kgf/25mm >10 伸长率 % >100

黏着力 kgf/25mm >1.0 剥离力 1-50 gf/25mm 高温保持力 11 mm

(25mmx25mmx1kgX80°Cx1hr)

击穿电压 kV >5

測試方法: 根據 ASTM 標準測試

保存期限: 12 個月(溫度: 23℃、濕度: 65%)

包裝標準: 每卷長 50M, 寬 1220MM, 卷心直徑 3 英寸

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or \*he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

