聚酯薄膜膠帶 產品編號:1P800 (阻燃)

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone : (852) 2604-8222 * Facsimile : (852) 3585 3181 E-mail : sales@pleo.com * Web Site : www.pleo.com



SL UL FILE #E126174

1P800 是 0.019 毫米厚的聚酯薄膜薄膜,塗有丙烯酸基熱固性壓敏黏合劑。傑出 產品描述:

的高溫物理和電氣性能保持力。本產品符合 UL 510 的阻燃要求。

應用: 用於高性能電氣應用,用於高溫線圈,例如曳引機製造、發電機、電容器變壓器等

的生產。

性能:

項目	單位	規格值
顏色	_	琥珀

總厚度 0.035 ± 0.005 mm

拉伸強度 >7 kgf/25mm 斷裂伸長率 >50

鋼板剝離力 0.45-1.0 kgf/25mm解卷力 gf/25mm250-900

擊穿電壓 k۷ >4 温度等級 130 o(;

常溫65%RH環境中,保質期自出廠日起6個月。 儲存條件:

33M 長, 3" 芯, 寬 1230 mm 規格:

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

