


TECHNICAL DATA

POLYIMIDE FILM TAPE

Product Code: 1K063A-3
(Flame Retardant)

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone : (852) 2604-8222 * Facsimile : (852) 3585 3181
E-mail : sales@pleo.com * Web Site : www.pleo.com



Description : 1K063A is a triple layer of 0.025mm thick (totally 0.075mm thick) Polyimide film coated with Silicone based thermosetting pressure sensitive adhesive.. This product complies with the flame Retardant requirements of UL 510.

Technical Data

<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
COLOR	-	amber
TOTAL THICKNESS	mm	0.195 ± 0.020
TENSILE STRENGTH	kgf/25mm	>10
ELONGATION	%	>20
ADHESION TO STEEL	kgf/25mm	>0.65
UNWIND FORCE	gf/25mm	600-1600
DIELECTRIC BREAKDOWN	kV	>6
TEMPERATURE RATED	°C	-

Test Method : In accordance with ASTM D-1000 method

Shelf Life : 6 months when storage at 73F and 65% relative humidity

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

