技術資料書

環氧塗覆 PET 聚酯膠帶

產品編號: 1SP10-3

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong. Telephone: (852) 2604-8222 * Fax: (852) 3585-3181 E-mail: sales@pleo.com * Web Site: www.pleo.com



FU UL FILE #E126174

說 明: 1SP10-3 是 0.390mm 厚度的乳白色膠帶,由塗有三層熱固性橡膠壓敏粘合劑的環

氧樹脂塗覆 PET 薄膜膠帶組成。常用於包裝繼電器、線圈、變壓器、繞線式次分

馬力罩極電機、棒繞或心軸繞線圈和線束。該膠帶通過了 UL 510 阻燃測試。

技術資料: 姓能 單位 規格

總厚度 mm 0.390

拉伸強度 N/25mm -

黏著力 kg/25mm(N/10mm) 2.85 (11.18)

擊穿電壓 kV ≥8

溫度等級 °C 155

CTI 等級 N/A I

測試方法: 溫度等級測試按照 UL 510, CTI 測試按照 IEC 60112, 其他測試按照 ASTM D-1000

保存期限: 6 個月(溫度:23℃、濕度:65%)

包裝標準: 每卷長 33M & 50M, 寬 960/1230mm, 卷心直徑 3 英寸

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness there of is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and nanufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

