

# TECHNICAL DATA

## POLYIMIDE FILM TAPE


Product Code: 1K030

### P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.

Telephone : (852) 2604-8222 \* Facsimile : (852) 3585 3181

E-mail : sales@pleo.com \* Web Site : www.pleo.com



**Description :** 1K030 is a 0.11mm thick Polyimide film coated with Silicone based thermosetting pressure sensitive adhesive °

#### Technical Details :

<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
COLOR	-	amber
BASE THICKNESS	mm	0.075±0.004
TOTAL THICKNESS	mm	0.110±0.005
TENSILE STRENGTH	N/25mm	> 200
ELONGATION	%	> 60
ADHESION TO STEEL	N/25mm	> 6.5
DIELECTRIC BREAKDOWN	kV	> 7.5
TEMPERATURE RATED	°C	-73~+260

**Test Method :** In accordance with ASTM D-1000 method

**Shelf Life :** 6 months when storage at 73F and 65% relative humidity

#### Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or \*he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

