


TECHNICAL DATA

POLYESTER FILM TAPE

Product Code: 1P801C
(Flame Retardant)

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone : (852) 2604-8222 * Facsimile : (852) 3585-3181
E-mail : sales@pleo.com * Web Site : www.pleo.com



Description : 1P801C(0.025mm film) coated with a pressure sensitive Acrylic adhesive, excellent adhesive properties, outstanding heat and Solvent resistant, high tensile strength and dielectric strength.

Application : Suitable for electrical products, such as capacitors and coil outer wrapping, to stabilize the transformer structure. It is used as insulation material of class B.

Technical Detail	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	TOTAL THICKNESS	mm	0.055±0.005
	TENSILE STRENGTH	kg/25mm	>9
	ELONGATION	%	>70
	ADHESION TO STEEL	kg/25mm	>0.8
	DIELECTRIC BREAKDOWN	kV	>5
	TEMPERATURE CLASS	°C	130
	CTI	—	PLC 0

Test Method : In accordance with ASTM method

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Availability : Standard 66M roll, 3" core, width 960mm/1230mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

以上僅供參考，如與英文版有歧異之處，一切內容以英文版為準

