

技术资料书

聚酯薄膜胶带 产品编号 : 1P801 (阻燃性)

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.

Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093

E-mail : sales@pleo.com * Web Site : http://www.pleo.com



UL FILE #E126174

说 明 : 1P801 聚酯薄膜胶带是在聚酯薄膜涂覆一层压敏丙烯酸酯胶粘剂而成, 具有良好的粘性、耐热、抗溶性、高拉伸强度和介电强度。本产品符合 UL510 阻燃的要求。

用 途 : 适用于变压器、电容器、电机、继电器、稳定器和各种电子组件上;
属于 B 级绝缘材料。

技术数据 :	性 能	单 位	规 格
	总厚度	mm	0.055±0.005
	拉伸强度	kg/25mm(lb/in)(N/10mm)	9.5(20.6)(37.24)
	伸长率	%	100±30
	黏着力	kg/25mm(oz/in)(N/10mm)	0.8(27.7)(3.13)
	击穿电压	kV	4
	耐热等级	°C	130

多种颜色 : RD = 红色 BK = 黑色 BL = 蓝色
WH = 白色 GR = 绿色

测试方法 : 根据 ASTM 标准测试

保存期限 : 6 个月 (温度: 23°C、湿度: 65%)

包装标准 : 每卷长 66M, 宽 960mm, 卷心直径 3 英寸

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

仅供参考, 如与英文版有歧异之处, 一切内容以英文版为准。



Copyright © P. LEO 2007 Rev. 4