

技術資料書

聚酯薄膜膠帶 產品編號:1P801 (阻燃性)



P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093
E-mail : sales@pleo.com * Web Site : http://www.pleo.com

UL FILE #E126174

說明 : 1P801 聚酯薄膜膠帶是在聚酯薄膜塗覆一層壓敏丙烯酸酯膠粘劑而成，具有良好的粘性、耐熱、抗溶性、高拉伸強度和介電強度。本產品符合 UL510 阻燃的要求。

用途 : 適用於變壓器、電容器、電機、繼電器、穩定器和各種電子元件上；屬於 B 級絕緣材料。

技術資料 :	性 能	單 位	規 格
	顏色	-	*如下參考
	總厚度	mm	0.055±0.005
	拉伸強度	kg/25mm (lb/in) (N/10mm)	9.5 (20.6) (37.24)
	伸長率	%	100±30
	黏著力	kg/25mm (oz/in) (N/10mm)	0.8 (27.7) (3.13)
	擊穿電壓	kV	4
	耐熱等級	°C	130

多種顏色 : RD=紅色 BK=黑色 BL=藍色
WH=白色 GR=綠色

測試方法 : 根據 ASTM 標準測試

保存期限 : 6 個月 (溫度: 23°C、濕度: 65%)

包裝標準 : 每卷長 66M, 寬 960mm, 卷心直徑 3 英寸

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

以上僅供參考，如與英文版有歧異之處，一切內容以英文版為準



Copyright © P. LEO 2007 Rev. 4